Protectosil® for Fiber Cement Boards



Protectosil® products render your fiber cement boards resistant against water, making them long lasting. Our Protectosil® brand offers several tailor-made solutions for your fiber cement boards, making them more resistant and durable while keeping them optically unchanged.

Evonik Silanes – Performance beyond expectations

• **•• ••** Protectosil®

Basic product recommendation

	Protectosil® grade	Effect			Processability	
	grade	Reduction of water uptake	Prevention of discoloration	Beading effect	Solvent for dilution	Recommended dilution rate
Pure silane systems	008	Ø			Organic solvent	Pure – 1:9
	009	Ø		Ø	Organic solvent	Pure – 1:9
	100 NK	Ø		⊘	Organic solvent	Pure – 1:9
Water based	WS 340	Ø			Water	1:1 – 1:3
	WS 410	Ø			Water	1:1.5 – 1:4
	WS 602	Ø			Water	1:1 – 1:4
	WS 610	⊘		Ø	Water	1:1.5 – 1:4
	WS 670	Ø			Water	1:1.5 – 1:4
	SC CONCENTRATE		Ø	Ø	Water	Pure – 1:10





Key benefits

- Excellent reduction of water uptake
- Variable penetration depth from few millimeters to full penetration depending on board type, product choice and application rate
- Effective protection against efflorescence
- Prevention of discoloration

Performance data


Reduction of water uptake





Penetration depth





Pictures above show treated test samples that were split with a hammer and chisel.

A water-based ink was then applied onto the fractured surface to visualize the penetration depth.

The inner part of the fiber cement boards where the concentration of the water repellent was not high enough to repel the water became colored, while the outer part near the substrate's suface did not absorb the colored water.

Evonik Operations GmbH Silanes Business Line Rodenbacher Chaussee 4 63457 Hanau-Wolfgang/Germany

protectosil@evonik.com

www.protectosil.com/en



This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. Evonik expressly disclaims any representations and warranties of any kind, whether express or implied, as to the accuracy, completeness, non-infringement, merchantability and/or fitness for a particular purpose (even if Evonik is aware of such purpose) with respect to any information and recommendations provided. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice. Protectosil® is a registered trademark of Evonik Industries AG or one of its subsidiaries.

FS-fibercementboards-en-03-2024/02-Pa

