## Protectosil® for Clay-Based Construction Materials



Protectosil® products upgrade clay-based construction materials such as roof tiles or bricks in durability and aesthetics.

Evonik Silanes – Performance beyond expectations

Protectosil®

## **Basic product recommendation**

Protectosil® grade	Type of tile		Effect				Treatment		Process	
	Natural	Engobed*	Hydropho- bation**	Beading/ Flow properties	Anti- greening	Consoli- dation	Spraying	Dipping	Production	On-Site
WS 340	<b>Ø</b>	<b>Ø</b>	<b>Ø</b>				<b>Ø</b>			<b>Ø</b>
WS 602	<b>Ø</b>	<b>Ø</b>	<b>Ø</b>				<b>Ø</b>	<b>Ø</b>	<b>Ø</b>	<b>Ø</b>
WS 610	<b>Ø</b>	<b>Ø</b>	<b>Ø</b>	<b>Ø</b>			<b>Ø</b>	<b>Ø</b>	<b>Ø</b>	<b>⊘</b>
WS 808	<b>Ø</b>		<b>Ø</b>	<b>Ø</b>		<b>Ø</b>	<b>Ø</b>		<b>Ø</b>	<b>Ø</b>
BHN	<b>Ø</b>	<b>Ø</b>	<b>Ø</b>				<b>Ø</b>			<b>Ø</b>
SC 60	<b>Ø</b>	<b>Ø</b>		<b>Ø</b>	<b>Ø</b>		<b>Ø</b>	<b>Ø</b>	<b>Ø</b>	<b>⊘</b>

\*Requires longer contact/immersion time

<sup>\*\*</sup> Significant long-term reduction of water uptake leads to reduction of efflorescence and freeze thaw damages




## **Key benefits**

- Reduction of water uptake > 90%
- Long-term protection due to high penetration depth, up to 2-25 mm
- Long-term surface functionality and aesthetic > 1500 QUV hours
- Reduction of white spotting

## Performance data

Reduction of water uptake







Protectosil® products for clay-based construction materials can be applied via spray application or immersion. In order to find the best production solution, we also provide different testing methods.

**Evonik Operations GmbH** Silanes Business Line Rodenbacher Chaussee 4 63457 Hanau-Wolfgang/Germany

protectosil@evonik.com

www.protectosil.com/en



This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. Evonik expressly disclaims any representations and warranties of any kind, whether express or implied, as to the accuracy, completeness, non-infringement, merchantability and/or fitness for a particular purpose (even if Evonik is aware of such purpose) with respect to any information and recommendations provided.

Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice. Protectosil® is a registered trademark of Evonik Industries AG or one of its subsidiaries.

FS-claybased construction-en-03-2024/02-Pa

